

## **Multi Function Testers**

## 6017/6018

- Designed to meet IEC 61010-1 CAT.III 600V
- Test leads with remote control switch. (For insulation&Simplified Earth Test)
- · Back light function.
- Color coded scales and range switch position for easy reading.
- Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance.
- Can be hung around the neck for both hand's operation.



Insulation Testing

6017 Test Voltage 125V/20MΩ

250V/50MΩ 500V/100MΩ 250V/50MΩ

6018 Test Voltage 250V/50MΩ

 $500 \text{V}/100 \text{M}\Omega$  $1000 \text{V}/2000 \text{M}\Omega$ 

Accuracy | ±5%rdg

Earth Resistance

Simplified Precision  $12\Omega/120\Omega/1200\Omega$ 

measurement

Accuracy | ±3% of full scale value

AC Voltage

0-600V AC |±3% of full scale value

Earth Voltage

0-60V AC |±3% of full scale value

General

Safety Standard IEC 61010-1 CAT.III 600V Pollution Degree 2

IEC 61010-2-031 IEC 61557

Withstand Voltage 5550V AC for 1 minute

Power Source LR6 (1.5V) × 8

Dimensions  $130(L) \times 183(W) \times 100(D)$ mm

Weight 1000g approx.

Accessories 7103A (Test leads with remote control switch),

7131B (Safety crocodile clip [black]), 7161A (Flat test bar [black]) 8017 (Extension prod), 9092 (Cord case), 9121 (Shoulder strap),

Battery LR6 (1.5V) × 8, Instruction Manual

Optional Accessories 7100 (Precision measurement Cord Set)