

MS890A



- Frequency 400Hz
- True RMS
- Overload Protection
- Transistor Test
- Diode
- Continuity
- LED
- Max Display: 2000
- CAT IV 600V / CAT III 1000V
- Relative
- Auto Power Off
- Data Hold
- Flashlight
- Battery: 9V

Spec	Range	Accuracy
Resistance	200Ω, 2KΩ, 20KΩ, 200KΩ, 2MΩ	±(0.8%+5)
	200MΩ	±(5.0%+10)
	200mV	±(0.5%+3)
DCV	2V, 20V, 200V	±(0.8%+3)
	1000V	±(1.0%+5)
	750V	±(1.2%+5)
ACV	2V, 20V, 200V	±(1.0%+5)
	750V	±(1.2%+5)
DCA	2mA, 200mA	±(1.0%+5)
	10A	±(1.5%+10)
ACA	2mA, 200mA	±(1.5%+5)
	10A	±(1.8%+15)
Capacitance	2nF	±(4.0%+20)
	20nF, 200nF, 2uF	±(4.0%+15)
	200uF	±(4.0%+20)
Frequency	200KHz	±(1.5%+10)
°C	-20°C~400°C	±(2.0%+3)
	400°C~1000°C	±(2.0%+3)

Packaging Information	
Accessories	Test leads, Manual, Temperature probe, 9V 6F22 Battery
Dimension	185*88*54mm
Weight	355g
Quantity	20
Color Box	118*58*195mm
Carton Box	420*325*260mm
SKU No.	MS890ACBGLO
EAN Code	8435394788333