

## testo 440 16 mm vane kit

## Kit for measurements in ventilation ducts

Structured measurement menu for volume flow

Determination of flow velocity in ventilation ducts

Built-in telescope which can be scaled up to 0.85 m

Internal data storage and USB port for data export

Can be extended with a large portfolio of digital probes











Compatible with a wide selection of Bluetooth® and wired probes.

With the testo 440 16 mm vane kit, all IAQ-related parameters in ventilation ducts can be measured and documented. The testo 440 air velocity & IAQ measuring instrument recognizes probes automatically, and its structured measurement menus simplify the adjustment of air conditioning and ventilation systems. Up to 3 probes can be connected simultaneously to the measuring instrument: a Bluetooth® probe, a wired probe and a temperature probe with Type K thermocouple connector.

In addition to the measuring instrument, the kit also contains a wired vane probe and a storage case.

## 1981 0674/msp/I/02.2019

Subject to change, including technical modifications.

## Scope of delivery

- testo 440 air velocity & IAQ measuring instrument, 3x AA batteries, USB cable and calibration protocol (0560 4401)
- Vane probe (Ø 16 mm) with fixed cable (cable length 1.7 m) including telescope (can be extended to 0.85 m) and calibration protocol (0635 9532)
- Basic case for testo 440 and 1 probe



Order no. 0563 4401

Technical data			Measuring range	Accuracy	Resolution
Digital probe					
Vane probe (Ø 16 mm) testo 440	300 to 850 mm Ø 12 mm	Ø 16 mm	0.6 to 50 m/s	±(0.2 m/s + 1 % of m.v.) (0.6 to 40 m/s) ±(0.2 m/s + 2 % of m.v.) (40.01 to 50 m/s)	0.1 m/s
testo 440 air velocity & IAQ measuring instrument Connectable probes: 1x digital probe with cable or 1x temperature NTC TUC, 1x digital Bluetooth® probe or Testo Smart Probes, 1x temperature TE Type K	GA- MI- MI-				

General technical data	testo 440	Vane probe (Ø 16 mm)	
Data transmission	Bluetooth®, USB interface		
Operating temperature	-20 to +50 °C	-10 to +70 °C	
Storage temperature	-20 to +50 °C	-10 to +70 °C	
Dimensions	154 x 65 x 32 mm	330 x 16 x 16 mm	
Probe head diameter		Ø 16 mm	
Weight	250 g	150 g	

You will find the complete selection of probes and accessories for the testo 440 in the testo 440 data sheet or at www.testo.com.

You will find the complete selection of probes and accessorie	S