

UT363S is a stable, safe and reliable split-type anemometer, featuring quick detection, low consumption and high accuracy. It can be widely used in mining, electrical, iron and steel, petrochemical, energy-saving, navigation, fan manufacturing, exhaust ventilation, sporting and more sectors.



UT363S

Specifications	Range	Accuracy
Certificates	CE, UKCA	
Wind speed	0.4~30m/s	±(5%+0.5m/s)
	1.4~108km/h	±(5%+1.5km/h)
	78~5905ft/min	±(5%+100ft/min)
	0.7~58knots	±(5%+1knots)
	0.8~67mph	±(5%+1mph)
Temperature	-10~50°C/14~122°F	±2°C/±4°F
Wind scale	0~12	±1
Sampling rate	0.5s	
Units	m/s, km/h, ft/min, knots, mph, °C/°F	
Working temperature	0°C~40°C	

Features	
Overload indication	Auto range/auto power off
Low battery indication	Data hold
MAX/MIN/AVG	Backlight

Characteristics	
Standard accessories	Batteries, English manual
Power	1.5V battery (R03) x 3
Display	35 x 32mm
Product size	120 x 53 x 43mm
Product net weight	365g
Standard individual packing	Gift box, blister
Standard quantity per carton	20pcs
Standard carton measurement	550 x 295 x 350mm
Standard carton gross weight	7.2kg